



- Lining Notes:**
- All Road Markings and Traffic Signs Drawings Should be Read in Conjunction with the Department of Transport Traffic Signs Manual (TSM)
 - All Signs Mounting Height Shall be 2300mm High & Have a minimum Clearance of 500mm from the Road side Edge unless stated otherwise
 - All Works shall be confirmed by the Employer's Representative prior to Commencement of Works
 - The Employer's Representative shall be Notified by the Contractor of any Errors or Omissions
 - Parking Restrictions line shall be as per RRM 007 & RRM 008 of the Traffic Signs Manual (TSM). Bound by a 100mm Wide Yellow Continuous line. To be situated 150mm - 300mm from Edge of Kerb. Location of Parking Restriction lines to be Agreed with Cork City Council
 - Hatching detail shall be as per FIG.7.13 to 7.18 and Table 7.5 of the Traffic Signs Manual, bound by a 150mm Wide Continuous White line & 100mm gap between Hatch and Boundary line as per RRM021
 - Parallel Parking Bays shall be as per RRM 011, RRM 012 & RRM 016 of the Traffic Signs Manual (TSM) & Bound by a 50mm Wide Continuous White line with a double 50mm white line at either end and 2m Buffer zone behind Disabled Parking bays with Yellow 50mm Wide Continuous Lines
 - Loading Bays shall be as per RRM 009 of the Traffic Signs Manual(TSM)
 - Disable Parking Bay shall comply with FIG.7.27 of the Traffic Signs Manual (TSM)

- Legend:**
- New Sign in 76mm Retention Socket
 - New 76mm Retention Socket
 - New Flexible Bolt Down Bollard
 - Worded STOP Marking 1600mm High as per M 114 of the TSM.
 - Worded NO ENTRY Marking as per M 114 of the TSM.
 - Bifurcation Arrows as per M 102 of the TSM.
 - Lane Indication Arrows (< 60km/h) 3600mm High as per RRM 004 of the TSM.
 - Lane Indication Arrows (< 60km/h) 3600mm High as per M 124 & M 125 of the TSM.
 - Cycle Symbol as per M 116 of the TSM.
 - Cycle Track Direction Arrow 1800 High as per M 118 of the TSM.
 - Cycle Triangular YIELD Marking 1875mm High as per M 115C of the TSM.
 - Disabled Parking Bay Symbol 2500mm High & 1200mm Wide as per RRM 015 of the TSM.
 - Bus Stop Finished With Red Coloured Surfacing
 - Traffic Signs Manual Line Marking Reference. (RRM 022)

| Rev | By | Date | Description |
|-----|----|----------|------------------|
| A | SL | 14-02-20 | Section 38 Issue |

CORK CITY COUNCIL
COMHAIRLE CATHRACH CHORCAÍ
INFRASTRUCTURE DEVELOPMENT DIRECTORATE,
CITY HALL,
CORK. Tel: 021 492 4019 Fax: 021 492 4018

CORK CITY COUNCIL
Infrastructure Development

INCLUDES ORDNANCE SURVEY IRLAND DATA REPRODUCED UNDER OS LICENCE NUMBER: 2019/01000/00000/00000000. UNAUTHORISED REPRODUCTION OF THIS DOCUMENT IS STRICTLY PROHIBITED. © ORDNANCE SURVEY IRELAND.

Contract: **Horgan's Quay Improvement Scheme**

Title: **Signs & Lining**

Scale: 1:750-A1
Date: Jan 20
Author: SL
Checked: JOL
Approved: JS

Project: LGR-HQ-02
Sheet: A