



**Cork
City Council**
Comhairle Cathrach Chorcaí

CLIENT:

PROJECT:

CNWQR Phase 1D East

DOCUMENT TITLE:

Services Report

DJF Engineering Services Ltd.
Tramore House, Reeveswood, Douglas Road, Cork, Ireland
Tel: 021-2392424 • Email: info@djfes.com • Web: www.djfes.com

| Current Issue | Date | Issue Description | Approvals | |
|---------------|----------|---------------------|-----------|----------|
| | | | By | Approved |
| P01 | 07/08/25 | Draft Issue | FH | SH |
| P02 | 25/09/25 | Issued for Planning | FH | SH |

CONTENTS

| | | |
|-----|---|----|
| 1.0 | Introduction | 4 |
| 1.1 | Background..... | 4 |
| 1.2 | Scope | 4 |
| 2.0 | Storm Water Discharge..... | 5 |
| 2.1 | General | 5 |
| 2.2 | Existing Drainage..... | 5 |
| 2.3 | Proposed Storm Water Drainage | 5 |
| 2.4 | Sustainable Urban Drainage Systems | 6 |
| 2.5 | Arbutus Drive Drainage | 6 |
| 3.0 | Foul Water Discharge..... | 8 |
| 3.1 | Existing Drainage..... | 8 |
| 3.2 | Proposed Foul Water Drainage | 8 |
| 4.0 | Water & Fire Fighting Supply..... | 9 |
| 4.1 | Water Supply | 9 |
| 4.2 | Fire Fighting Supply..... | 9 |
| 5.0 | Site Layout..... | 10 |
| 5.1 | General | 10 |
| 5.2 | Road Layout..... | 10 |
| 6.0 | Historical Aerial Photo of the Site..... | 11 |
| 6.1 | General | 11 |
| 7.0 | Proposed Drainage Layout..... | 12 |
| 7.1 | General | 12 |
| 8.0 | Proposed Watermain Layout | 12 |
| 8.1 | General | 12 |
| 9.0 | Appendices..... | 12 |
| 9.1 | Met Eireann Rainfall Data..... | 13 |
| 9.2 | SuDS calculations for permeable surfacing to walkways & patios..... | 14 |
| 9.3 | Plane infiltration system calculations for Houses 1 to 5 | 15 |
| 9.4 | Plane infiltration system calculations for Houses 6 to 11 | 16 |

| | | |
|------|--|----|
| 9.5 | SuDS infiltration calculation for 300mm diam. Pipe | 17 |
| 9.6 | QBAR calculation | 18 |
| 9.7 | Storm water attenuation calculation | 19 |
| 9.8 | Storm water network calculations | 20 |
| 9.9 | Foul water network calculations..... | 21 |
| 9.10 | Uisce Eireann Confirmation of Feasibility | 22 |

1.0 INTRODUCTION

1.1 Background

Cork City Council intend to construct 14 no. new dwellings on a brown field site on Dunmore Gardens. The proposed development consists of:

- a 3-storey apartment block with 3 no. 2-bedroom units (one on the ground floor apartment and two no. duplex apartments over)
- an adjoining terrace of 6 no. 3-storey, 3-bedroom houses
- a terrace of 5 no. 2-storey, 3-bedroom houses

Cork City Council have engaged DJF Engineering Services Ltd. to provide Engineering services in relation to the preparation of the information package for this development.

1.2 Cork City North West Quarter Regeneration

This project forms part of the CNWQR. Subsequent phases of the CNWQR will include works to the roads and services immediately to the north and east of the site. These works will include road realignment works and the provision of separated main drainage systems.

The services have been designed to connect to the existing combined sewers in this area while allowing for future connections to new downstream separated main drainage systems constructed as part of future phases of the CNWQR scheme.

1.3 Scope

This Services Report sets out the Engineering approach taken for the proposed development in relation to storm water discharge, foul water discharge, and water & fire fighting supply.

2.0 STORM WATER DISCHARGE

2.1 General

This section sets out how storm water from rainfall on roofs and new hardstanding areas associated with the new development is proposed to be dealt with.

2.2 Existing Drainage

The existing drainage system on Dunmore Gardens is a combined system with storm water and foul water discharging to a combined sewer. There is also a combined sewer under Kilmore Road Lower to the south.

2.3 Proposed Storm Water Drainage

From previous site investigations on the site, the site is underlain by sands and gravels. These soils have a high permeability and therefore an increased capacity for storm water discharge. Further site testing in accordance with BRE Digest is proposed in advance of detailed design. For the purpose of this report, conservative values for soil permeability have been assumed and used in the calculations in the appendices.

Given the limited plot sizes due to the requirements for housing density, it is proposed to discharge storm water from the rear roofs of the housing units to ground via plane infiltration systems positioned in the rear garden of each house.

The proposed storm water design includes several SuDS measures to limit the inflow of storm water to the existing combined sewer network in the area.

These include:

- plane infiltration devices where space is available in the rear gardens of the houses to discharge storm water from rear roofs of houses to ground.
- permeable surfacing for private paths and patios

- perforated oversized pipe to allow infiltration of storm water from the front roofs, the roof of the apartment block and driveways to ground for storm events up to 6 months while also providing attenuation for storm events up to the 100 year storm event. This pipe will be perforated and bedded in filter material and allow for infiltration to ground. Discharge flows from this pipe to the existing combined sewer will also be limited by a "hydrobrake" type flow limiting device to provide attenuation.

Calculations for the proposed plane infiltration systems, and for the oversized pipe for attenuation are included in the appendices. All storm water systems proposed are designed for a 100 year storm plus 20% increase in rainfall depth (for climate change).

2.4 Sustainable Urban Drainage Systems

The proposed storm water design includes several SuDS measures to limit the inflow of storm water to the existing combined sewer network in the area.

These include:

- plane infiltration devices where space is available in the rear gardens of the houses to discharge storm water from rear roofs of houses to ground.
- permeable surfacing for private paths and patios
- perforated oversized pipe to allow infiltration of storm water from the front roofs, the roof of the apartment block and driveways to ground for storm events up to 6 months while also providing attenuation for storm events up to the 100 year storm event.

2.5 Arbutus Drive Drainage

The proposed site layout includes a new cul-de-sac on the eastern side of the site. A later phase of the City North West Quarter Regeneration will involve the

extension of this cul-de-sac to the south to form Arbutus Drive. The location and orientation of this cul-de-sac has been set out as per the CNWQR masterplan.

Existing services in this area limit the space for a connection to the existing combined sewer to the north on Dunmore Gardens. Therefore, as a temporary measure until later phases of the CNWQR are completed, it is proposed to connect the two no. proposed stormwater gullies on the cul-de-sac to the existing combined sewer on Kilmore Road Lower. The storm sewer on the cul-de-sac is to be extended in later phases of the CNWQR when this cul-de-sac will be extended to form Arbutus Drive.

3.0 FOUL WATER DISCHARGE

3.1 Existing Drainage

The existing drainage system on Dunmore Gardens is a combined system.

3.2 Proposed Foul Water Drainage

It is proposed to extend the existing combined system west under Dunmore Gardens to allow for connections to the proposed western terrace of 5 no. 2-storey houses. All other units are proposed to connect to the existing combined sewer in accordance with Uisce Eireann details.

A pre-connection enquiry to Uisce Eireann has been submitted for this development. The Uisce Éireann Pre-Connection Enquiry Reference Number is CDS250004613. A confirmation of feasibility has subsequently been received from Uisce Eireann.

4.0 WATER & FIRE FIGHTING SUPPLY

4.1 Water Supply

There is currently no existing Uisce Éireann water supply to the site. It is proposed to connect to the existing watermain on Dunmore Gardens to the north of the site.

A pre-connection enquiry to Uisce Eireann has been submitted for this development. The Uisce Éireann Pre-Connection Enquiry Reference Number is CDS250004613. A confirmation of feasibility has subsequently been received from Uisce Eireann.

4.2 Fire Fighting Supply

There are several existing fire hydrants available for fire fighting in the vicinity of the development. Refer to DJF drawing 5027-DJF-EXE_0-DR-C-0003 for details. No additional fire hydrants are proposed as all housing units are within 46m of an existing hydrant.

5.0 SITE LAYOUT

5.1 General

Refer to Cork City Council Architect's Site Layout drawing.

5.2 Road Layout

The proposed site layout includes a new cul-de-sac on the eastern side of the site. A later phase of the City North West Quarter Regeneration will involve the extension of this cul-de-sac to the south to form Arbutus Drive. The location and orientation of this cul-de-sac has been set out as per the CNWQR masterplan.

The site layout for this development including driveways and front boundary walls allows for the later development of Christy O'Shea Road to the north of the development as part of subsequent phases of the CNWQR. The future Christy O'Shea Road is planned to replace the existing Dunmore Gardens road to the north of the site and is planned to include a cycle path as well as footpaths and green verges.

6.0 HISTORICAL AERIAL PHOTO OF THE SITE

6.1 General

From Geohive MapGenie Imagery (1996-2000):



7.0 PROPOSED DRAINAGE LAYOUT

7.1 General

Refer to DJF drawings 5027-DJF-EXE-_0-DR-C-0001 & 5027-DJF-EXE-_0-DR-C-0002 for details of the proposed storm and foul drainage.

8.0 PROPOSED WATERMAIN LAYOUT

8.1 General

Refer to DJF drawing 5027-DJF-EXE-_0-DR-C-0003 for details of the existing and proposed water main layout.

9.0 APPENDICES

See overleaf.

9.1 Met Eireann Rainfall Data

Met Eireann Rainfall Depths For Sliding Durations
Irish Grid: Easting: 165779, Northing: 73147,

| DURATION | Interval | Years | | | | | | | | | |
|----------|---------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| | | 2, | 3, | 4, | 5, | 10, | 20, | 30, | 50, | 75, | 100, |
| 5 mins | 3.1, 4.1, | 4.6, | 5.3, | 5.9, | 6.2, | 7.5, | 8.8, | 9.7, | 10.9, | 11.9, | 12.7, |
| 10 mins | 4.3, 5.7, | 6.4, | 7.5, | 8.2, | 8.7, | 10.4, | 12.3, | 13.5, | 15.2, | 16.6, | 17.7, |
| 15 mins | 5.0, 6.7, | 7.5, | 8.8, | 9.6, | 10.2, | 12.2, | 14.4, | 15.9, | 17.8, | 19.5, | 20.8, |
| 30 mins | 6.7, 8.8, | 9.9, | 11.5, | 12.5, | 13.3, | 15.8, | 18.5, | 20.3, | 22.7, | 24.3, | 25.6, |
| 1 hours | 9.0, 11.7, | 13.1, | 15.0, | 16.3, | 17.3, | 20.4, | 23.8, | 25.9, | 28.8, | 29.7, | 30.5, |
| 2 hours | 12.1, 15.5, | 17.2, | 19.7, | 21.3, | 22.6, | 26.4, | 30.5, | 33.1, | 36.7, | 39.7, | 42.0, |
| 3 hours | 14.4, 18.3, | 20.3, | 23.1, | 24.9, | 26.3, | 30.7, | 35.3, | 38.3, | 42.2, | 45.7, | 48.2, |
| 4 hours | 16.2, 20.6, | 22.8, | 25.9, | 27.9, | 29.4, | 34.1, | 39.2, | 42.4, | 46.7, | 50.4, | 53.2, |
| 6 hours | 19.3, 24.3, | 26.8, | 30.3, | 32.6, | 34.3, | 39.7, | 45.4, | 49.0, | 53.8, | 57.9, | 61.0, |
| 9 hours | 22.9, 28.7, | 31.5, | 35.5, | 38.1, | 40.1, | 46.1, | 52.5, | 56.5, | 61.9, | 66.5, | 70.0, |
| 12 hours | 25.9, 32.2, | 35.4, | 39.8, | 42.6, | 44.7, | 51.4, | 58.3, | 62.6, | 68.5, | 73.5, | 77.2, |
| 18 hours | 30.8, 38.0, | 41.6, | 46.6, | 49.8, | 52.3, | 59.7, | 67.5, | 72.4, | 78.9, | 84.9, | 88.6, |
| 24 hours | 34.8, 42.8, | 46.7, | 52.2, | 55.7, | 58.3, | 66.5, | 74.9, | 80.2, | 87.2, | 93.2, | 97.7, |
| 2 days | 44.0, 53.4, | 57.9, | 64.3, | 68.3, | 71.3, | 80.6, | 90.1, | 96.0, | 103.9, | 110.6, | 115.5, |
| 3 days | 51.7, 62.2, | 67.3, | 74.3, | 78.8, | 82.1, | 92.3, | 102.8, | 109.2, | 117.8, | 125.0, | 130.4, |
| 4 days | 58.5, 70.0, | 75.6, | 83.3, | 88.1, | 91.7, | 102.7, | 114.0, | 120.9, | 130.1, | 137.8, | 143.6, |
| 6 days | 70.7, 84.0, | 90.4, | 99.1, | 104.6, | 108.7, | 121.2, | 133.9, | 141.6, | 151.9, | 160.5, | 166.9, |
| 8 days | 81.8, 96.6, | 103.6, | 113.3, | 119.4, | 124.0, | 137.6, | 151.6, | 160.1, | 171.3, | 180.7, | 197.6, |
| 10 days | 92.1, 108.3, | 116.0, | 126.5, | 133.1, | 138.0, | 152.9, | 167.9, | 177.1, | 189.2, | 199.3, | 206.7, |
| 12 days | 101.8, 119.3, | 127.6, | 138.9, | 146.1, | 151.3, | 167.2, | 183.3, | 193.1, | 206.0, | 216.7, | 224.6, |
| 16 days | 120.2, 140.1, | 149.4, | 162.2, | 170.2, | 176.1, | 193.9, | 211.9, | 222.8, | 237.1, | 249.0, | 257.8, |
| 20 days | 137.5, 159.5, | 169.9, | 184.0, | 192.8, | 199.3, | 218.9, | 238.6, | 250.5, | 266.1, | 279.1, | 288.6, |
| 25 days | 158.2, 182.7, | 194.2, | 209.8, | 219.6, | 226.9, | 248.3, | 270.0, | 283.1, | 300.2, | 314.4, | 324.8, |

NOTES:

N/A Data not available

These values are derived from a Depth Duration Frequency (DDF) Model

For details refer to:

Fitzgerald D. L. (2007), Estimates of Point Rainfall Frequencies, Technical Note No. 61, Met Eireann, Dublin,
Available for download at www.met.ie/climate/data/products/Estimation-of-Point-Rainfall-Frequencies_TN61.pdf

9.2 SuDS calculations for permeable surfacing to walkways & patios

HYDRAULIC CALCULATION FOR SUDS COMPONENTS: PERMEABLE SURFACE CONSTRUCTED WITH NATURAL STONE OR FLAGS WITH 10MM THICK SPACERS SYSTEM A - TOTAL INFILTRATION FOR BACK PATIOS AND WALKWAYS AROUND HOUSES AND APARTMENT BLOCK

Infiltration rate: 1.0E-06 m / sec = 0.003600 m / h

Note: For details please refer to Ground Investigation Report: infiltration rate for sandy gravelly clay

n - total porosity of system directly over infiltration base 0.30
q - infiltration coefficient: 0.003600 m/h
A_D - area to be drained: 319 m²
R - Run-off Co-efficient: 0.90
A_b - base area of infiltration system: 255 m²
R - drainage ratio = A_D/A_b 1.13

$$H_{\max} = (D \times (R \times I - q)) / n$$

| D - storm duration | Rainfall (100 year storm + 20% increase in depth (climate change)) Return Period Rainfall Depths for sliding Durations Irish Grid: Easting: 165779, Northing: 073147 | i - rainfall intensity | H _{max} - maximum depth of water in sub-base with 30% air voids |
|--------------------|--|------------------------|--|
| [h] | [m] | [m/h] | [m] |
| 0.083 | 0.0152 | 0.1829 | 0.056 |
| 0.2 | 0.0212 | 0.1274 | 0.078 |
| 0.3 | 0.0250 | 0.0998 | 0.091 |
| 0.5 | 0.0316 | 0.0631 | 0.112 |
| 1.0 | 0.0400 | 0.0400 | 0.138 |
| 2.0 | 0.0504 | 0.0252 | 0.165 |
| 3.0 | 0.0578 | 0.0193 | 0.181 |
| 4.0 | 0.0638 | 0.0160 | 0.191 |
| 6.0 | 0.0732 | 0.0122 | 0.203 |
| 9.0 | 0.0840 | 0.0093 | 0.207 |
| 12.0 | 0.0926 | 0.0077 | 0.203 |
| 18.0 | 0.1063 | 0.0059 | 0.183 |
| 24.0 | 0.1172 | 0.0049 | 0.152 |
| 48.0 | 0.1386 | 0.0029 | 0.056 |
| 72.0 | 0.1565 | 0.0022 | 0.277 |
| 96.0 | 0.1723 | 0.0018 | 0.506 |
| 144.0 | 0.2003 | 0.0014 | 0.977 |
| 192.0 | 0.2251 | 0.0012 | 1.460 |
| 240.0 | 0.2480 | 0.0010 | 1.950 |
| 288.0 | 0.2695 | 0.0009 | 2.445 |
| 384.0 | 0.3094 | 0.0008 | 3.448 |
| 480.0 | 0.3463 | 0.0007 | 4.461 |
| 600.0 | 0.3898 | 0.0006 | 5.738 |

From table above, H_{max} is:

0.207 m

9.3 Plane infiltration system calculations for Houses 1 to 5

HYDRAULIC CALCULATION FOR SUDS COMPONENTS: PLANE INFILTRATION SYSTEMS AT THE BACK GARDENS FOR HOUSES 1 TO 5

Infiltration rate: 1.0E-06 m / sec = 0.003600 m / h

Note: For details please refer to Ground Investigation Report: infiltration rate for sandy gravelly clay

| | |
|--|--------------------|
| n - total porosity of system directly over infiltration base | 0.40 |
| q - infiltration coefficient: | 0.003600 m/h |
| A _D - area to be drained: | 30 m ² |
| R - Run-off Co-efficient: | 0.90 |
| A _b - base area of infiltration system: | 8.0 m ² |
| R - drainage ratio = A _D /A _b | 3.40 |

$$H_{\max} = (D \times (R \times I - q))/n$$

| D - storm duration | Rainfall (100 year storm + 20% increase in depth (climate change)) | | i - rainfall intensity | H _{max} - maximum depth of water in sub-base with 40% air voids |
|--------------------|--|--------|------------------------|--|
| | [h] | [m] | | |
| 0.083 | | 0.0152 | 0.1829 | 0.129 |
| 0.2 | | 0.0212 | 0.1274 | 0.179 |
| 0.3 | | 0.0250 | 0.0998 | 0.210 |
| 0.5 | | 0.0316 | 0.0631 | 0.264 |
| 1.0 | | 0.0400 | 0.0400 | 0.330 |
| 2.0 | | 0.0504 | 0.0252 | 0.410 |
| 3.0 | | 0.0578 | 0.0193 | 0.464 |
| 4.0 | | 0.0638 | 0.0160 | 0.506 |
| 6.0 | | 0.0732 | 0.0122 | 0.568 |
| 9.0 | | 0.0840 | 0.0093 | 0.632 |
| 12.0 | | 0.0926 | 0.0077 | 0.679 |
| 18.0 | | 0.1063 | 0.0059 | 0.741 |
| 24.0 | | 0.1172 | 0.0049 | 0.780 |
| 48.0 | | 0.1386 | 0.0029 | 0.745 |
| 72.0 | | 0.1565 | 0.0022 | 0.681 |
| 96.0 | | 0.1723 | 0.0018 | 0.600 |
| 144.0 | | 0.2003 | 0.0014 | 0.405 |
| 192.0 | | 0.2251 | 0.0012 | 0.184 |
| 240.0 | | 0.2480 | 0.0010 | 0.053 |
| 288.0 | | 0.2695 | 0.0009 | 0.303 |
| 384.0 | | 0.3094 | 0.0008 | 0.828 |
| 480.0 | | 0.3463 | 0.0007 | 1.378 |
| 600.0 | | 0.3898 | 0.0006 | 2.089 |

From table above, H_{max} is:

0.780 m

9.4 Plane infiltration system calculations for Houses 6 to 11

HYDRAULIC CALCULATION FOR SUDS COMPONENTS: PLANE INFILTRATION SYSTEMS AT THE BACK GARDENS FOR HOUSES 6 TO 11

Infiltration rate: 1.0E-06 m / sec = 0.003600 m / h

Note: For details please refer to Ground Investigation Report: infiltration rate for sandy gravelly clay

| | |
|--|--------------------|
| n - total porosity of system directly over infiltration base | 0.40 |
| q - infiltration coefficient: | 0.003600 m/h |
| A _D - area to be drained: | 24 m ² |
| R - Run-off Co-efficient: | 0.90 |
| A _b - base area of infiltration system: | 6.5 m ² |
| R - drainage ratio = A _D /A _b | 3.29 |

$$H_{\max} = (D \times (R \times I - q)) / n$$

| D - storm duration | Rainfall (100 year storm + 20% increase in depth (climate change)) Return Period Rainfall Depths for sliding Durations Irish Grid: Easting: 165779, Northing: 073147 | i - rainfall intensity | H _{max} - maximum depth of water in sub-base with 40% air voids |
|--------------------|--|------------------------|--|
| [h] | [m] | [m/h] | [m] |
| 0.083 | 0.0152 | 0.1829 | 0.125 |
| 0.2 | 0.0212 | 0.1274 | 0.173 |
| 0.3 | 0.0250 | 0.0998 | 0.203 |
| 0.5 | 0.0316 | 0.0631 | 0.255 |
| 1.0 | 0.0400 | 0.0400 | 0.320 |
| 2.0 | 0.0504 | 0.0252 | 0.397 |
| 3.0 | 0.0578 | 0.0193 | 0.449 |
| 4.0 | 0.0638 | 0.0160 | 0.489 |
| 6.0 | 0.0732 | 0.0122 | 0.548 |
| 9.0 | 0.0840 | 0.0093 | 0.610 |
| 12.0 | 0.0926 | 0.0077 | 0.654 |
| 18.0 | 0.1063 | 0.0059 | 0.713 |
| 24.0 | 0.1172 | 0.0049 | 0.749 |
| 48.0 | 0.1386 | 0.0029 | 0.709 |
| 72.0 | 0.1565 | 0.0022 | 0.640 |
| 96.0 | 0.1723 | 0.0018 | 0.554 |
| 144.0 | 0.2003 | 0.0014 | 0.352 |
| 192.0 | 0.2251 | 0.0012 | 0.125 |
| 240.0 | 0.2480 | 0.0010 | 0.119 |
| 288.0 | 0.2695 | 0.0009 | 0.374 |
| 384.0 | 0.3094 | 0.0008 | 0.910 |
| 480.0 | 0.3463 | 0.0007 | 1.470 |
| 600.0 | 0.3898 | 0.0006 | 2.193 |

From table above, H_{max} is:

0.749 m

9.5 SuDS infiltration calculation for 300mm diam. Pipe

HYDRAULIC CALCULATION FOR SUDS COMPONENTS: PROPOSED 300Ø UPVC PERFORATED PIPE LAID IN 900 WIDE X 600 HIGH TRENCH FILLED WITH FILTER MATERIAL TO CLAUSE 505 TYPE B WITH 40% AIR VOIDS

Infiltration rate: 1.0E-06 m / sec = 0.003600 m / h

Note: For details please refer to Ground Investigation Report: infiltration rate for sandy gravelly clay

| | |
|--|--------------------|
| n - total porosity of system directly over infiltration base | 0.48 |
| q - infiltration coefficient: | 0.003600 m/h |
| A _D - area to be drained: | 820 m ² |
| R - Run-off Co-efficient: | 0.90 |
| A _b - base area of infiltration system: | 73 m ² |
| R - drainage ratio = A _D /A _b | 10.05 |

$$H_{\max} = (D \times (R \times I - q)) / n$$

| D - storm duration | Rainfall (6 months storm + 20% increase in depth (climate change)) Return Period Rainfall Depths for sliding Durations Irish Grid: Easting: 165779, Northing: 073147 | i - rainfall intensity | H _{max} - maximum depth of water in system |
|--------------------|--|------------------------|---|
| [h] | [m] | [m/h] | [m] |
| 0.083 | 0.0032 | 0.0389 | 0.067 |
| 0.2 | 0.0044 | 0.0266 | 0.092 |
| 0.3 | 0.0053 | 0.0211 | 0.109 |
| 0.5 | 0.0070 | 0.0139 | 0.142 |
| 1.0 | 0.0092 | 0.0092 | 0.186 |
| 2.0 | 0.0124 | 0.0062 | 0.244 |
| 3.0 | 0.0145 | 0.0048 | 0.281 |
| 4.0 | 0.0164 | 0.0041 | 0.314 |
| 6.0 | 0.0194 | 0.0032 | 0.362 |
| 9.0 | 0.0229 | 0.0025 | 0.412 |
| 12.0 | 0.0258 | 0.0022 | 0.450 |
| 18.0 | 0.0305 | 0.0017 | 0.503 |
| 24.0 | 0.0344 | 0.0014 | 0.541 |
| 48.0 | 0.0425 | 0.0009 | 0.529 |
| 72.0 | 0.0492 | 0.0007 | 0.490 |
| 96.0 | 0.0553 | 0.0006 | 0.438 |
| 144.0 | 0.0661 | 0.0005 | 0.304 |
| 192.0 | 0.0760 | 0.0004 | 0.150 |
| 240.0 | 0.0852 | 0.0004 | 0.016 |
| 288.0 | 0.0938 | 0.0003 | 0.195 |
| 384.0 | 0.1102 | 0.0003 | 0.574 |
| 480.0 | 0.1255 | 0.0003 | 0.972 |
| 600.0 | 0.1439 | 0.0002 | 1.488 |

From table above, H_{max} is:

0.541 m

9.6 QBAR calculation

Report IoH 124 Method of Calculating Q_{bar}

SOIL INDEX

$S_1 \dots S_5$ denotes the proportions of the catchment covered by each of the soil classes 1 to 5.

| | | |
|---------|-------|------------------------|
| $S_1 =$ | 0 % | |
| $S_2 =$ | 0 % | |
| $S_3 =$ | 0 % | |
| $S_4 =$ | 100 % | RUNOFF POTENTIAL: HIGH |
| $S_5 =$ | 0 % | |

$$(0.15S_1 + 0.30S_2 + 0.40S_3 + 0.45S_4 + 0.5S_5)$$

$$\text{SOIL} = S_1 + S_2 + S_3 + S_4 + S_5$$

$$\text{SOIL} = 0.45 \%$$

$$\text{AREA} = 0.5 \text{ Km}^2 \quad 50 \text{ Ha}$$

$$\text{SAAR} = 1089 \text{ mm} \quad \begin{array}{l} \text{MET EIREANN DATA} \\ \text{Irish Grid: Easting: 166000, Northing:} \\ 73000 \end{array}$$

$$Q_{bar} = 0.00108 \times (\text{AREA km}^2)^{0.89} \times (\text{SAAR mm})^{1.17} \times (\text{SOIL \%})^{2.17}$$

$$Q_{bar} = 0.368 \text{ m}^3/\text{s} \quad 368.4 \text{ l/s} \quad 7.4 \text{ l/s/ha}$$

9.7 Storm water attenuation calculation

STORM WATER ATTENUTATION CALCULATION FOR PROPOSED 300Ø UPVC PERFORATED PIPE LAID IN 900 WIDE X 600 HIGH TRENCH FILLED WITH FILTER MATERIAL TO CLAUSE 505 TYPE B WITH 40% AIR VOIDS

Total Site Area = 2,321 m²
 Total Site Area = 0.2321 ha
 Q_{bar} 7.4 l/s/ha
 Below calculation are for proposed warehouse extension:
 100 year throttle rate growth curve factor (Irish) = 1.90
 100 year greenfield limiting discharge rate = 3.3 l/s

| Catchment area description | Area (m ²) | Runoff coefficient | Net Area (m ²) |
|---|------------------------|--------------------|----------------------------|
| Front roofs of houses + whole roof of apartment block | 428.2 | 0.90 | 385.4 |
| Private driveways | 391.4 | 0.90 | 352.3 |
| TOTAL: | 819.6 | | 737.6 |

100 year storm + 20% increase for climate change in rainfall depth

Permissible Volume (l)= Actual Achievable Outflow (l/s) x time (s)
 Actual Volume (l)= (Impermeable Area x depth of rainfall)
 Storage capacity (l)= Actual - Permissible Volumes

Rainfall data:

Met Eireann Return Period Rainfall Depths for sliding Durations
Irish Grid: Easting: 165779, Northing: 73147

| Duration min | Rainfall mm | Permissible Volume | Actual Volume | Storage capacity |
|-----------------|----------------|-----------------------|------------------|---------------------|
| | | m ³ | m ³ | m ³ |
| 5 | 15.240 | 1.0 | 11.2 | 10.3 |
| 10 | 21.240 | 2.0 | 15.7 | 13.7 |
| 15 | 24.960 | 2.9 | 18.4 | 15.5 |
| 30 | 31.560 | 5.9 | 23.3 | 17.4 |
| 60 | 39.960 | 11.7 | 29.5 | 17.7 |
| 120 | 50.400 | 23.5 | 37.2 | 13.7 |
| 180 | 57.840 | 35.2 | 42.7 | 7.4 |
| 240 | 63.840 | 47.0 | 47.1 | 0.1 |
| 360 | 73.200 | 70.5 | 54.0 | 16.5 |
| 540 | 84.000 | 105.7 | 62.0 | 43.8 |
| 720 | 92.640 | 141.0 | 68.3 | 72.6 |
| 1,080 | 106.320 | 211.5 | 78.4 | 133.0 |
| 1,440 | 117.240 | 282.0 | 86.5 | 195.5 |
| 2,880 | 138.600 | 563.9 | 102.2 | 461.7 |
| 4,320 | 156.480 | 845.9 | 115.4 | 730.4 |
| 5,760 | 172.320 | 1,127.8 | 127.1 | 1,000.7 |
| 8,640 | 200.280 | 1,691.7 | 147.7 | 1,544.0 |
| 11,520 | 225.120 | 2,255.6 | 166.1 | 2,089.6 |
| 14,400 | 248.040 | 2,819.5 | 183.0 | 2,636.5 |
| 17,280 | 269.520 | 3,383.4 | 198.8 | 3,184.6 |
| 23,040 | 309.360 | 4,511.2 | 228.2 | 4,283.0 |
| 28,800 | 346.320 | 5,639.0 | 255.5 | 5,383.6 |
| 36,000 | 389.760 | 7,048.8 | 287.5 | 6,761.3 |

From table above, required storage volume is:

17.7 m³

From table above, critical storm duration is :

60 min

Maximum hydrobrake discharge :

3.3 l/s

9.8 Storm water network calculations

Rainfall Intensity roof = 75 mm/hr
 Rainfall Intensity paved = 50 mm/hr
 Storm Return Period = 5 years
 Self cleansing Velocity = 0.8-3 m/s
 Roof Vol. run-off coefficient = 0.9
 Paved Vol. run-off coefficient = 0.9
 Pipe Roughness K_s = 0.6 mm

| Pipe No. | Impermeable Area (A_p) | Gradient | Diameter | Actual Rate of Flow | Accumulative Rate of Flow | Discharge Velocity | Capacity Full bore flow | Full Bore Velocity | Proportional flow | Discharge Velocity | Proportional Depth |
|----------|-------------------------------|-----------------------|----------|------------------------|------------------------------|-----------------------|-------------------------------|-----------------------|----------------------|-----------------------|-----------------------|
| | Roof (A_{p1}) | Paved (A_{p2}) | | Q | Q_t | v | Q_p | v_p | Q/Q_p | | |
| | m^2 | m^2 | 1 lin | mm | l/s | l/s | l/s | l/s | OK? | OK? | OK? |
| S1-S2 | 151 | 209 | 40 | 300 | 5.4 | 5.4 | 1.13 | 176.0 | 2.49 | OK | OK |
| S2-S3-S4 | 293 | 391 | 80 | 300 | 10.4 | 10.4 | 1.08 | 124.2 | 1.76 | OK | OK |
| S4-S5-S6 | 428 | 391 | 100 | 300 | 12.9 | 12.9 | 1.06 | 111.0 | 1.57 | OK | OK |
| S6-S7 | | | 60 | 225 | 3.3 | 3.3 | 0.88 | 67.2 | 1.69 | OK | OK |

9.9 Foul water network calculations

Number of Discharge Units per Dwelling:
 Self cleansing velocity when flowing half full:
 Pipe Roughness Co-efficient (K_s):

14
 0.75 to 3
 m/s
 for < 30 units
 0.6
 1.5
 for > 30 units

| Pipe No. | Accumulative No. of residential units | Irish Water | | Building Regulations | | BS 8301:1985 | | Number of Discharge units | Actual | Full Bore | | Proportional flow | Proportional Depth | Proposed Network | | | |
|--|---------------------------------------|-------------|------------|----------------------|------------|--------------|------------|---------------------------|--------|---------------------|-------------------------|-------------------|--------------------|------------------|-----|-----|-----|
| | | Fall | Internal Ø | Fall | Internal Ø | Flow Q | Velocity v | | | Flow Q _o | Velocity v _o | | | | | | |
| P | No. | 1 in | mm | 1 in | mm | 1 in | mm | units | units | l/s | m/s | l/s | m/s | OK? | OK? | OK? | OK? |
| WASTEWATER OUTLET FROM EACH HOUSE | 1.0 | N/A | N/A | 60 | 100 | 90 | 100 | 14 | 2.59 | 0.77 | 6.35 | 0.81 | OK | OK | OK | OK | |
| WASTEWATER OUTLET APARTMENT BLOCK (3 APARTMENTS) | 3.0 | 60 | 150 | 100 | 100 | 100 | 150 | 42 | 3.19 | 0.76 | 17.72 | 1.00 | OK | OK | OK | OK | |

9.10 Uisce Eireann Confirmation of Feasibility



CONFIRMATION OF FEASIBILITY

Fergus Humphries

Tramore House
Reeveswood
Douglas Road
Cork
T12R8XW

15 July 2025

Uisce Éireann
Bosca OP 448
Oifig Sheachadta na
Cathrach Theas
Cathair Chorcaí

Uisce Éireann
PO Box 448
South City
Delivery Office
Cork City

www.water.ie

Our Ref: CDS25004613 Pre-Connection Enquiry
Site at, Knocknaheeny, Dunmore Gardens, Cork City

Dear Applicant/Agent,

We have completed the review of the Pre-Connection Enquiry.

Uisce Éireann has reviewed the pre-connection enquiry in relation to a Water & Wastewater connection for a Housing Development of 14 unit(s) at Site at, Knocknaheeny, Dunmore Gardens, Cork City, (the **Development**).

Based upon the details provided we can advise the following regarding connecting to the networks;

- **Water Connection** - Feasible without infrastructure upgrade by Uisce Éireann
- **Wastewater Connection** - Feasible without infrastructure upgrade by Uisce Éireann

This letter does not constitute an offer, in whole or in part, to provide a connection to any Uisce Éireann infrastructure. Before the Development can be connected to our network(s) you must submit a connection application and be granted and sign a connection agreement with Uisce Éireann.

As the network capacity changes constantly, this review is only valid at the time of its completion. As soon as planning permission has been granted for the Development, a completed connection application should be submitted. The connection application is available at www.water.ie/connections/get-connected/

Stiúrthóiri / Directors: Niall Gleeson (POF / CEO), Jerry Grant (Cathaoirleach / Chairperson), Gerard Britchfield, Liz Joyce, Michael Nolan, Patricia King, Eileen Maher, Cathy Mannion, Paul Reid, Michael Walsh.
Oifig Chláraithe / Registered Office: Teach Colvill, 24-26 Sráid Thalbóid, Baile Átha Cliath 1, D01 NP86 / Colvill House, 24-26 Talbot Street, Dublin, Ireland D01NP86
 Is cuideachta ghníomhaiochta ainmnithe atá fací theorainn scaireanna é Uisce Éireann / Uisce Éireann is a designated activity company, limited by shares.
 Cláraithe in Éirinn Uimh.: 530363 / Registered in Ireland No.: 530363.

UF / LR / OP448 / 0323

Where can you find more information?

- **Section A** - What is important to know?

This letter is issued to provide information about the current feasibility of the proposed connection(s) to Uisce Éireann's network(s). This is not a connection offer and capacity in Uisce Éireann's network(s) may only be secured by entering into a connection agreement with Uisce Éireann.

For any further information, visit www.water.ie/connections, email newconnections@water.ie or contact 1800 278 278.

Yours sincerely,



Dermot Phelan
Connections Delivery Manager